

TAB Journal




THE MAGAZINE OF THE ASSOCIATED AIR BALANCE COUNCIL • WINTER 2015

Instrumentation & Equipment for Proper Balancing

IN THIS ISSUE:

- Sheave and Belt Changes
- Differences in Digital Multimeters
- Micron Filters

**A MUST-HAVE RESOURCE FOR
INDUSTRY PROFESSIONALS!**



**Over 350 pages of standards
for total system balancing.
Order your copy of the AABC
National Standards for Total
System Balance today!**

The AABC National Standards for Total System Balance

The AABC National Standards for Total System Balance, 2002 edition, is a comprehensive manual detailing the minimum standards for total system balance.

Each chapter covers a specific area in the test and balance process, enabling the design professional to select those items that are best suited for a particular project.

Additionally, the Standards will assist the design professional in achieving design intent, provide a better understanding of the scope of work required of the TAB agency, and ensure that proper methods and procedures are followed in the test and balance process.

Features of the Standards include:

- Illustrative tables and charts
- Equations and examples
- Sample specifications
- Expanded section of sample report forms
- New technologies, such as DDC
- Updated testing procedures
- Appendix with equations in both English and Metric formats

AABC believes that by promoting the concept of Total System Balance, the industry will be encouraged to adopt more consistent practices, thus ensuring greater success for all parties involved in the design, installation, start-up, operation and testing of HVAC systems.



For additional information on the Associated Air Balance Council or the new AABC Standards, visit our website at www.aabc.com, or contact AABC National Headquarters at **202-737-0202**.

Payment Information:

Non-Member Cost: \$75.00

AABC National Standards 2002 @ \$75 each x _____ = \$ _____

Name

Company

Shipping Address

City State Zip

Phone Fax

Email

Payment Type (Check one)

Check Enclosed MasterCard Visa American Express

Card Number Expiration Date

Name on Card

Signature

Please complete order form and return along with payment to:



Associated Air Balance Council

1518 K Street, N.W., Suite 503 • Washington, D.C. 20005

Credit card purchasers may fax orders to: (202) 638-4833
or order online at www.aabc.com/publications

TAB Journal

Associated Air Balance Council

BOARD OF DIRECTORS AND OFFICERS

President

Daniel J. Aciri
Flood and Sterling Inc.

Executive Vice President

Michael L. Delcamp
National Precisionaire, LLC

Secretary/Treasurer

Benjiman J. Link
United Testing & Balancing, Inc.

Vice President/Eastern Zone-1

Michael S. Kelly
American Testing Inc.

Vice President/Central Zone-2

Douglas R. Meacham
Kahoe Air Balance Company

Vice President/Western Zone-3

Gaylon Richardson
Engineered Air Balance Co. Inc.

Immediate Past President

Jay A. Johnson
Thermal Balance, Inc.

Director, Canadian Chapter

Donald F. C. Mowat
D. F. C. Mechanical Testing & Balancing Ltd.

Executive Director

Kenneth M. Sufka

Editorial Director

Ray Bert

TAB Journal Editor

Ashley Weber

Technical Advisor

Joseph E. Baumgartner, III, P.E.

Editorial Office

1518 K Street, N.W., Suite 503
Washington, D.C. 20005
(202) 737-0202 • FAX: (202) 638-4833
E-mail: info@aabc.com
Website: www.aabc.com

TAB Journal is published quarterly by the Associated Air Balance Council. It is distributed free to AABC members and by subscription to non-members at \$24 per year. *TAB Journal* is an open forum for the free expression of opinions and information. The views expressed are not necessarily those of AABC, its officers, directors, or staff. Letters, manuscripts, and other submissions are welcome. However, *TAB Journal* accepts no responsibility for unsolicited material. All rights reserved. Copyright © 2014 by the Associated Air Balance Council.

TAB INTERACTIVE



Scan this code to
view the *TAB Journal*
online archives.

ECO BOX

TAB Journal magazine text and cover pages are printed on SFI-certified Anthem Gloss paper using soy ink.



SFI standards conserve biodiversity and protect soil and water quality, as well as wildlife habitats.

The SFI certified sourcing label is proof AABC is using fiber from responsible and legal sources.

SFI participants also plant more than 650 million trees each year to keep these forests thriving.

The Dirt on Micron Filters 3

Mike Van Wiechen, TBS
Airwaso Canada Inc.

The Importance of Correct Airflow Monitoring Stations: A Case Study 7

Benjiman J. Link, TBE
United Testing & Balancing, Inc.

Issues with Specified Room Pressures 9

Douglas R. Meacham, TBE
Kahoe Air Balance Company

Project Specifications: Friend or Foe? 11

Baltimore Air Balance Company

Sheave & Belt Change Issues 13

Don Burke, TBE
PBC, Inc.

Is Your Amp Meter Lying to You? A Field Test Experiment to Highlight the Differences of True RMS and Non-True RMS Digital Multimeters 16

Lowell T. Hedrick, Jr., P.E., CxA and Patrick E. Young, TBE, CxA
Test and Balance Corporation

From the Publisher

The winter 2015 issue of *TAB Journal* looks at some of the instrumentation and equipment encountered in testing and balancing projects. Mike Van Weichen, TBS of *Airwaso Canada Inc.* discusses the use of micron filters in filtration systems.


Benjiman J. Link, TBE of *United Testing & Balancing, Inc.* goes into the importance of correct airflow monitoring stations and the problems that can arise if these are not maintained and cleaned properly.

Also in this issue, Douglas R. Meacham, TBE of *Kahoe Air Balance Company* looks at how room construction can affect the design pressure criteria.

In "Project Specifications: Friend or Foe?" the Baltimore Air Balance Company makes the case for a thorough review of plans and specifications before beginning any project.

Don Burk, TBE of *PBC, Inc.* discusses who should bear labor and material costs in test and balance projects that require fan sheave and belt replacements.

Lowell T. Hedrick, Jr., TBE, CxA and Patrick E. Young, TBE, CxA of *Test and Balance Corporation* compare the differences between true RMS and non-true RMS digital multimeters in digital volt-amp meter measurements.

We would like to thank all of the authors for their contributions to this issue of *TAB Journal*. Please contact us with any comments, article suggestions, or questions to be addressed in a future Tech Talk. We look forward to hearing from you! 

The system pump flow rate should include the filter flow requirement. The result will be flow rates at the terminals not being compromised by keeping the system clean.



The Dirt on MICRON FILTERS

Mike Van Wiechen, TBS
Airwaso Canada Inc.



Many hydronic systems have filtration systems in place that clean and filter the water. Typical systems use strainers and micron filters to achieve cleanliness.

Strainers are usually found at the pump inlet. Mesh size may be 1/8 inch. Startup strainers are used during the filling, flushing and cleaning stage to remove construction contaminants.

Initial TAB system pre-checks require the TAB technician to inspect this strainer to ensure it is clean, and that the correct mesh size is in place.

Micron filters are either installed side stream to the pump, or more commonly across the pump with flow from the pump discharge piping, to filter, to pump suction piping (*Figure 1*). Typically, they are installed near the chemical feed pump and share common piping. Ball valves isolate the filter for easier cartridge replacement.

Cartridges are made with a variety of materials (Cotton, Glass, Nylon, Polyester, Rayon), and with different pore sizes (1 to 150 microns). Most common are cartridges made of Cotton string, wound on a 2 1/2" diameter by 10 inch spool and have a retention from 5 to 20 microns. Pressure drops can vary from 1 psi to 20 psi depending on flow rates and particle loading.

During the TAB balancing of the system, the filter is normally isolated from the system. Design engineers usually size the circulation pump flow rate, for the design sum of the terminals (coils, convectors, radiant panels, chilled beams, etc.).

No consideration is usually given for the flow rate required for the filter to keep the system clean. Micron filter flow may divert 10% or more of the pump flow rate. We have never encountered a project where an engineer had specified the filter flow rate, or sized a system pump to include filter flow rate.

In some cases a CBV (circuit balance valve) was installed in the micron filter piping, but this will not maintain a constant flow rate as the filter loads.

In other instances a sight glass (with floating ball indicator) was installed at the outlet side of the filter. Maintenance staff can manually adjust one of the isolation valves daily to ensure flow.

The best solution would be a sight glass and a pressure independent flow control valve (automated balancing valve). This would be selected based on the required flow rate of the filter, and be installed on the downstream side of the filter. With this set up, flow rate remains constant as the filter loads and pump motor VFD ramps up and down.

The maintenance mechanic has an indicator of when the filter is fully loaded when the sight glass is not indicating flow. Once again, the system pump flow rate should include the filter flow requirement. The result will be flow rates at the terminals not being compromised by keeping the system clean. ☀





Figure 1.

TABPRO

TRAINING SERIES

Save 10% when you order all three TABpro DVDs!

You'll get lessons on standard VAVs, parallel fan-powered VAVs, standard duct leakage testing, pressure decay leakage testing, and basic psychrometrics.



Bundle (VAV, Duct Leakage & Psychrometrics)

3 DVDs
 Total run time 106 minutes
 List price: \$468.00
 Member price: \$351.00



Basic Psychrometrics

DVD format
 Run time: 19 minutes
 List price: \$120.00
 Member price: \$90.00

This volume contains one lesson on basic psychrometrics. This provides the viewer with an introduction to psychrometric fundamentals and takes you through five of the basic elements found on the psychrometric chart. This lesson will break down these elements on the chart and provide fundamental concepts of chart usage.

Duct Leakage and Pressure Decay Testing

DVD format
 Run time: 42 minutes
 List price: \$200.00
 Member price: \$150.00

This volume consists of two lessons covering standard duct leakage testing and pressure decay leakage testing. These lessons take the viewer through an introduction to leakage testing, essential job preparation, instrumentation used during testing, general procedures for leakage testing, multiple calculations used during testing and final reporting.

Variable Air Volume (VAV) Terminals

DVD format
 Run time: 45 minutes
 List price: \$200.00
 Member price: \$150.00

This volume consists of two lessons covering standard VAVs and parallel fan-powered VAVs, both using DDC controls. These lessons take the viewer through an introduction to VAV terminals, essential job preparation, instrumentation used during testing, general procedures for testing and balancing, and final reporting.

Quantity	Title	Price	
		Non-Member	Member
_____	Psychrometrics	\$120	\$90
_____	Duct Leakage	\$200	\$150
_____	VAV Terminals	\$200	\$150
_____	Bundle of all 3 DVDs	\$468	\$351

Total: \$ _____

Payment Information

Payment Type (Check one)
 Check Enclosed MC Visa AMEX

Card Number _____

Expiration Date _____

Name on Card _____

Signature _____

Please complete order form and return along with payment to:

Associated Air Balance Council
 1518 K Street, N.W., Suite 503
 Washington, D.C. 20005

Credit card purchasers may fax orders to: (202) 638-4833 or order online at www.aabc.com/publications

Shipping Information

Name _____ Phone _____

Company _____ Fax _____

Shipping Address _____ E-mail _____

City/State/Zip _____

CX ENERGY 2015

CONFERENCE & EXPO

APRIL 27-30, 2015

Join us for the premier
Conference & Expo for
building commissioning
and energy management.

Discover state of
the art equipment,
instrumentation, and
technology. Learn from
industry experts on topics
designed to enhance
your business.

SUPPORTING ORGANIZATIONS



ENERGY MANAGEMENT
ASSOCIATION



By overwhelming demand... CxENERGY IS BACK!

The Premier Event for Building
Commissioning & Energy Management

WHO attends CxENERGY?

- Commissioning Providers
- Operations & Maintenance Managers
- Energy Managers
- Building Owners & Managers
- Architects
- Consulting Engineers
- Manufacturers
- Energy Service Providers
- Government Officials
- Financial Experts



EVENT LOCATION:

Green Valley Ranch in Henderson, NV,
located minutes from the Las Vegas strip.

Register to attend before March 15 and
save 10% with promo code **TAB10**

WHO should Sponsor & Exhibit?

Manufacturers and Providers of:

- HVAC Systems
- Building Automation Systems
- Sensors & Monitors
- Energy Meters & Tools
- Building Envelope Services
- Lighting
- Design Tools
- Insulation & Ducting Systems
- Geothermal Technologies
- Software

Visit www.CxEnergy.com,
info@commissioning.org or call 202.737.7775

The Importance of Correct Airflow Monitoring Stations: A CASE STUDY

Benjiman J. Link, TBE
United Testing & Balancing, Inc.



How does a healthcare facility that has been occupied only seven months, balanced and recalibrated by the same TAB agency have such severe pressurization problems?

With the high cost of investigative testing and troubleshooting, the vital role of Airflow Monitoring Station cannot be overlooked. The following example may help TAB agencies, Mechanical Engineers, and Owners find a simple fix to a serious problem.

A healthcare facility requested assistance with a problem where spaces had become improperly pressurized with high humidity levels, leading to excessive condensation. The ceiling tiles throughout the facility were in need of replacement, sometimes on a daily basis, due to staining from the excessive moisture. Overall, the facility was in an uncomfortable condition.

The initial visit confirmed the owner and occupant's complaints – an isolation room had water dripping from the ceiling and was under an extreme negative pressure. Initially, the temperature set point had been lowered in the space to help with patient comfort, but the room had to be vacated due to the conditions. Above the ceiling, all of the exposed ductwork was covered in condensation.

The second room observed had the same pressure and humidity issues as the first. The supply duct in the area had condensation which filled the duct-mounted smoke detector casing. The relative humidity level measured above the ceiling was 81%. At this point, condensation was dripping from the duct through the ceiling to the floor.

The building was relatively new and had been completely balanced within the last year. It is equipped with an Energy Management System (EMS) where multiple values including air quantities, temperatures, etc., could be monitored. During initial review of the EMS, all of the control set points, outside air volumes, and unit operations appeared to be correct. The sum of the outside air introduced to the building was 42,000 CFM, in accordance with the original design. All of the discharge air temperatures were maintaining set points, and there

were no other apparent issues that could cause the types of problems observed in the patient rooms.

Further investigation revealed the area of the building with the most prevalent moisture issues was $-0.06''$ w.c. in relation to the atmosphere. This information led to examination of the associated RTU. The outside air design quantity for the unit was 7,000 CFM. The same correction factors recorded in the TAB report were still in place and had not been changed in the Airflow Monitoring Stations (AFMS). The visual displays for the AFMS confirmed the airflow offset was 7,000 CFM between the supply and return fans, and the EMS confirmed the same information.

Velocities at the fresh air intake were found to be very low. A suggestion was made to the owner that the AFMS should be recalibrated using the same method performed for the original TAB project. After recalibration, the space was $+0.03''$ w.c. in relation to the atmosphere.

Although the issues with the RTU had been corrected, whenever adjacent doors were opened to other areas in the facility, the negative conditions would present themselves again. Following a complete pressure survey of the facility, it was found that all areas had negative pressure problems related to AFMS that were not controlling to the correct outside air quantity.

It was finally recommended to the owner that all of the AFMS be cleaned and recalibrated. When this was completed, the overall building was positively pressurized at $+0.03''$ w.c. The pressure relationships between different areas of the building were correct. Room pressure monitors were now within normal ranges, humidity levels were as expected for July and there were no problems with condensation.

So how does a healthcare facility that has been occupied only seven months, balanced and recalibrated by the same TAB agency have such severe pressurization problems?

The particular airflow sensing devices for this facility are glass bulb thermal dispersion sensors. During the cleaning of the flow stations for the recalibration purposes, some of the bulbs were found to have a buildup of dirt and lint. This continual buildup was causing incorrect airflow

CORRECTION FACTORS

RTU #	Original Correction	Area Correction
RTU-1 (Supply)	2.83	2.83
RTU-1 (Return)	2.17	2.56
RTU-2 (Supply)	4.07	4.55
RTU-2 (Return)	4.17	5.00
RTU-3 (Supply)	2.47	2.07
RTU-3 (Return)	1.40	1.62
RTU-4 (Supply)	4.57	3.63
RTU-4 (Return)	3.03	3.75
RTU-5 (Supply)	8.60	6.16
RTU-5 (Return)	4.33	5.03
RTU-6 (Supply)	4.70	4.70
RTU-6 (Return)	4.15	3.90
RTU-7 (Supply)	1.44	1.78
RTU-7 (Return)	1.23	1.52
RTU-8 (Supply)	1.96	2.34
RTU-8 (Return)	1.85	1.99
RTU-9 (Supply)	5.63	6.44
RTU-9 (Return)	4.93	5.64
RTU-10 (Supply)	2.11	2.35
RTU-10 (Return)	1.85	1.80
RTU-11 (Supply)	4.04	3.47
RTU-11 (Return)	2.90	2.90
RTU-12 (Supply)	3.49	2.70
RTU-12 (Return)	2.26	2.34

measurements, and in this situation, a vast reduction of outside airflow. Based on all of the information gathered it was assumed that the combination of construction completion, and the introduction of new linens to the facility had caused an unusually high level of airborne particulates. This resulted in a need for flow station cleaning long before expected.

The provided chart, (*left*), shows the original TAB report correction factors and the new correction factors after the cleaning and recalibration. It was also noted that there may have been buildup of particulates, due to temporary filters and normal construction practices that affected the original TAB correction factors.

RECOMMENDATIONS

Even with a short duration of occupancy, some circumstances will require cleaning of Airflow Monitoring Stations long before an experienced TAB agency would expect. The following recommendations offer guidance to help prevent issues with AFMS.

- Always follow the manufacturer's recommendations for maintenance and cleaning of AFMS.
- Detailed inspection of flow stations for cleanliness before initial TAB is recommended.
- Periodic verification of Airflow Monitoring Stations by a certified AABC TAB agency is always a good idea. 🌐

Need a Better Test & Balance Spec? AABC CAN HELP!

- Specify for Independence
- Detailed contractor responsibilities to ensure system readiness for T&B
- Recommended, achievable tolerances
- Detailed procedural requirements
- AIA format, MasterSpec approved



For more information: www.aabc.com/specs

Email headquarters@aabc.com, or call 202-737-0202



Issues with Specified Room Pressures

Douglas R. Meacham, TBE
Kahoe Air Balance Company

Not all rooms are built the same. Testing room pressures at a hospital, research lab, or even at a pharmaceutical manufacturing facility can reveal differences. Technicians can encounter room pressure requirements specified for a room without specified criteria as to the tightness of the room's envelope. If the room is not treated as a vessel, with all penetrations accounted for, then that room will have issues attaining any stated pressure. It is necessary for the design engineer and the architect to have the same intention on the space requirements. If there is a pressure requirement, then a room construction requirement needs to be specified as well. This can be accomplished with stating that all areas surrounding pressure zones need a rated barrier or wall.


With this requirement, attention to items—such as cinderblocks needing to be sealed, all conduit penetrations requiring sealing, walls needing to extend to the deck, and doors needing to be gasketed—are part of the original design documents. Now a calculated offset can accomplish the required function, creating a pressure relationship. With all of the energy-saving requirements that are driving the construction industry today, having a space that requires additional supply or exhaust to satisfy a room pressure will require additional energy to operate because it was not appropriately designed architecturally.

For instance, a recent project involved a lab that was designed to be negative 0.05" w.c. with a 100 CFM offset and utilizing a supply AV and an Exhaust EV for control. This room had no construction specifications other than that of a typical office wall with standard doors and an acoustical drop ceiling. To achieve a negative pressure in the room, it was directed that the supply be reduced by 10% and exhaust be increased by 10%. However, the exhaust system was already operating at its maximum speed and a 10% increase in the exhaust could not be achieved. Under the new conditions the room pressure was -0.01" w.c., with close to a 200 CFM offset. Using Blower Door, it was calculated that an offset of 354 CFM was needed to achieve a -0.05" w.c. room pressure.


Inspecting the room and surrounding areas it was determined that the space needed to be constructed tighter. To accomplish this the facility maintenance contractor did the following:

- Installed a foiled back ceiling tile into a gasketed ceiling grid
- Added door sweeps and gaskets
- Sealed off light switches and electrical outlets

The room was re-tested using the Blower Door to verify that there were positive results after the space changes. The room achieved a -.05" w.c. room pressure with a 90 CFM offset. The space conditions were met with even less airflow making it more efficient.

It is always a good idea to verify how the room construction will affect the design pressure criteria. 

If there is a pressure requirement, then a room construction requirement needs to be specified as well.



The adage goes, “there is no such thing as a bad question” and the earlier a question is asked, the better.

PROJECT SPECIFICATIONS: Friend or Foe?

Baltimore Air Balance Company

For all contractors, every project should start with a thorough review of the project's plans and specifications. As TAB agencies, the plans show what needs to be balanced, and the specification (specs) gives the details on the testing, balancing and other test requirements.

A proper review of the specifications starts with the estimator. It is the job of the estimator to cover all the requirements set forth by the design engineer. After all, it is the design engineer that will be reviewing the submittals and final TAB report at the end of the project. Do not take shortcuts before a project is even started. Have everything covered that is required by the project's specifications in the proposal. With that being said, there can be some unorthodox requirements in the TAB spec. As strange as it may seem to take vibration measurements on a fractional horsepower motor, if it's in the spec, make sure it is covered in the proposal. When bringing attention to something provide separate pricing for the testing that is deemed "over the top". That way the requirements of the project are accounted for.

The next step begins when a project is awarded. Again review the plans and specs and make sure the team understands what is required. Many specs call for qualifications to be submitted along with the procedures used to test and balance each system. The AABC certifications cover all the qualifications that are needed as an independent Testing and Balancing agency. The procedures are a little more involved, but do not take shortcuts if the specs require the submission of the procedures used to balance the project. Provide detailed procedures for each system on the project. Some specs ask for a detailed design review as well. It is a good practice to perform a design review even if the requirement isn't detailed in the TAB section of the specifications.

This last step before the actual balancing can save lost time at the end of the project, waiting for responses from the engineer of record on questions that could have been asked early on in the job. The main things to call out are the need for additional balancing devices, the amount of diversity in each variable volume system, differences between the total connected flow and the output of fans and pumps in constant volume systems, possible building pressurization problems, etc. The adage goes, "there is no such thing as a bad question" and the earlier a question is asked, the better.

When called to start balancing the TAB Technician should again review the specifications before actually starting any test and balance work. This will make sure it is understood what scope of work must be performed. This will also ensure the Technician has all the equipment to take the measurements that are required. The attention to detail saves time in the long run, avoiding a possible return to the site after balancing is complete.

Lastly, after the TAB work is done and the report complete, it is the Test and Balance Engineer's turn to review the specifications before certifying the TAB report. This is all in the name of providing what is required, while also delivering a quality TAB report in the most efficient way possible. If there isn't time to do it right the first time, when will there be time to do it a second time?

Is the testing and balancing specification section a TAB Agency's friend or foe? As with many things in the world, it is a matter of perspective. Someone who takes shortcuts may find the specs unreasonable when the design engineer forces them to take all the required data. However, if all the data is recorded thoroughly the first time around, specs can be a good guideline to the entire team working to provide the building owner with a quality product. ●





Sheave & Belt Change Issues

Don Burke, TBE
PBC, Inc.

During the process of testing and balancing air systems, it is not uncommon to find that achievement of design air requirements necessitates the changing of the fan's sheave and belts. In these cases, three questions that need to be answered often come up: **1)** Who should size the new sheave and belts, **2)** who should install them and **3)** who should pay the labor and material costs?

In the vast majority of cases, the answer to the first two questions is the TAB agency. Experience has taught that sizing new sheave and belt combinations based on actual field test results is the way to assure expediency with the fewest mistakes. Installing the new sheave and belt combination should also be done by the TAB agency, since they must retest the system afterwards.

Regarding the third question: Who should pay the labor and material costs—the answer is not as simple.

To come up with a sensible answer based on practical realities, the following postulates should be considered:

- 1.** Most TAB agencies do not include the cost of sheave and belt changes in their price unless specifically called

for by specification—i.e., existing AC-1 will require a sheave and belt change in order to increase/decrease air output to the new design requirements.

- 2.** The reason TAB agencies cannot include the costs of sheave and belt changes in their price is simple. Many times, fans that require sheave and belt changes are relatively simple systems, systems for which the total price to balance is less than the costs of labor and material to change the sheave and belt. Even for many more extensive systems, the costs of sheave and belt changes can amount to 25% or more of the cost to test and balance the system.

Obviously, the potential cost of sheave and belt changes cannot be included in the balancing price nor imposed upon the balancing agency without an unfair financial burden upon the TAB agency.

- 3.** Who should bear the cost of sheave and belt changes? Customarily the mechanical contractor pays these costs. Since the gross costs of a system including the air handlers, the piping, ductwork, etc., are all normally included in the mechanical contractor's price,



the cost of a sheave and belt change is usually a very small percentage of overall costs; and, therefore, not too significant either at bid time or relative to profit margin.


Although the mechanical contractor customarily pays for sheave and belt changes, that does not clearly answer the question of who should pay. That question has several different answers depending on the reason a sheave and belt must be changed.

Following are several examples:

- a. The fan's design calls for 5000 CFM at 1.0" ESP and 1000 RPM. Tests show the fan delivers 6000 CFM at 1.5" ESP and 1200 RPM, and the adjustable sheave is at minimum adjustment. Who should be responsible for the sheave change? The fan manufacturer or his representative, because design RPM cannot be reached.
- b. The fan's design is the same as in a., above. Tests show

the fan delivers 4000 CFM at 1.5" ESP and 1075 RPM and the adjustable sheave is at maximum adjustment. Evidence shows that because of unforeseen field conditions, some of the ductwork had to be modified in such a way as to create more than anticipated resistance. Who should be responsible for the sheave change? Most likely the mechanical contractor, because it is for this type of situation that the design engineer wants protection for himself and the owner. The designer expects the mechanical contractor to allow for situations such as this in his price so that the owner need not be charged additionally.

- c. The fan's design calls for 5000 CFM at 2.0" S.P. and 1000 RPM. Tests show the fan delivers 6000 CFM at 0.5" ESP and 925 RPM, and the adjustable sheave is at minimum adjustment. Who should pay for the sheave and belt change? If the duct system is installed essentially as designed, the design engineer should be



responsible for the sheave and belt change. If actual ESP is less than 0.5" at design air (5000 CFM) but design stated 2.0" ESP, the error is in the design.

In no case should the costs of sheave and belt changes be imposed upon the TAB agency unless it was known before bid time that specific units would require these changes, and the TAB agency was asked to include these costs in their bid.

SUMMARY

Reasons Why Sheave And V-Belt Changes Are Necessary

1. Field conditions necessitate duct changes that impose more static pressure (SP) resistance.
2. The design engineer overestimated or underestimated the SP resistance of the system.
3. The fan is shipped from the manufacturer with a sheave and belt combination that does not permit adjustments capable of achieving design RPM's.

4. The fan is capable of running at or above design RPM and is seeing design or less than design SP, yet does not deliver design CFM.
5. The fan's connected airflow requirement is significantly above or below the fan's design CFM.
6. The fan is an existing system and the design engineer states in the balancing specification that sheave and belt changes, if necessary, are to be included as part of the balancing.
7. System effect factors result in CFM output deficiencies.

COMMENTARY

Except for a situation such as described in number 6, above, there is no circumstance in which the cost of a sheave and V-belt change should be imposed upon the balancing agency. 🌐

Troubleshooting motors fed by adjustable speed controllers can be difficult if you do not utilize the right meter.

INTRODUCTION

The two methods generally used in Digital Volt-Amp Meter (DVM) measurement electronics are:

1. Non-True RMS (root mean square) - AC average rectified measurement.
2. True RMS measurement.

Troubleshooting motors fed by adjustable speed controllers can be difficult if you do not utilize the right meter. Solid state motor drives and controls often conduct non-sinusoidal (distorted) current. Distorted current waveforms occur in short pulses rather than the smooth sine wave seen with a standard induction motor or a resistive heater. The measurement differences between true RMS and non-true RMS meters can affect proper motor adjustments. A non-true RMS meter inaccurately measures non-pure sinusoidal waveforms due to limitations of the electronics and poor signal representation. These meters are specified to be “average responding-RMS indicating.” They capture the rectified average of an AC waveform and scale the number by 1.1 to calculate the RMS value. In other words, the value they display is not a true value, but is a calculated value based on an assumption about the wave shape. The average responding method works for pure sine waves, such as heaters and induction motors, but can lead to large reading errors up to 40 percent, when a waveform is distorted by nonlinear loads such as adjustable speed drives or computers. For this article, motor amperages will be compared using a True RMS DVM meter and a DVM using averaging rectified amperage and voltage measurements. The test will demonstrate that using a non-true RMS meter can result in “overloading” a motor above its full load amperage (FLA) eventually causing failure.

EXPERIMENT

The experiment is designed to show the differences of true RMS and non-true RMS (AC rectified averaging) digital multimeters. The test starts with a fan motor that had failed, was replaced with a new motor and placed back in operation. Measurements will be taken as the speed of the fan is adjusted by use of a single phase diode rectifying controller. This test will also show the correlation of the fan’s speed, amperage and airflow. Equipment used in this experiment include:

1. A Greenheck Model CUE 121-A-G Fan, The motor is rated at ½ HP, 115 volt and 6 full load amps, equipped with Vari-Speed Controller which generated a non-pure sinusoidal waveform from the AC incoming line voltage.
2. A Shortridge Digital Multimeter with Vel-Grid attachment and static probe.
3. A Southwire 21010N AC average rectified digital multimeter.
4. A Fluke 376 True RMS digital multimeter.

Meters were clamped around same conductor to measure the output current from the speed controller to the fan motor. These results were consistent and repeatable within the tested equipment and instrument tolerances, and can be used as a quick guide to differentiate between true RMS and average rectified multimeters.

The test was conducted on an oven hood fan supplied with a Greenheck CUE 121 equipped with a variable speed controller. Described below are three different methods to determine the oven hood airflow. The average of all three was calculated to be 1,492 CFM. The fan static pressure was measured at .92” w.g. at 6.0 amps and 123.5 volts. This would indicate that the ½ horsepower motor was fully loaded. Plotting the airflow data on the manufacturer’s fan curve shows it does not fall properly on the curve. It is believed that this discrepancy can be accounted for in that the 10” round duct rises to the bottom of the curb where it opens to the full curb size, thus most likely causing some level of “system effect” on the fan. This does not account for the electrical issues noted below with regard to the speed controller.



Figure 1.

Measuring the same motor current with two meters: Which one is correct? The motor circuit above feeds a motor via a speed controller with a non-linear load with “distorted” current wave. The true-RMS clamp reads correctly but the average responding clamp reads low by 27 percent.

MECHANICAL MEASUREMENTS OF AIRFLOW - GREENHECK CUE 121-A-G

The velocity was measured at the 10” round inlet using Shortridge Multimeter and airflow was noted as 2,647 FPM multiplied times 0.545 sq. ft. = 1,443 CFM. Second, the 10” round duct connection was measured using a Shortridge Multimeter with the static probe as noted on hood label. The baseline value noted on the nameplate tag was that 0.40” which equates to 900 CFM. Since 1.15” w.g. was measured at the duct collar, this would calculate to 1,526 CFM. A third check was completed using the Shortridge Multimeter and the Vel-Grid attachment on the face of the perforated face of the hood intake. Avg. Velocity = 317 FPM x 4.75 sq. ft. (Intake area 57” X 12”) = 1,506 CFM. The static pressure was measured at 0.92”w.g.

ELECTRICAL MEASUREMENTS

The steady state operating conditions of the oven fan motor and “Vari-Speed” controller were utilized. The motor is rated at ½ HP, 115 volt and 6.0 full load amps. Using the current triac controls, the Vari-Speed would allow operating amperage up to approximately 10 amps or 167% of rated full load amps. The motor speed/amp curve, as was measured, is an inverted “V” with “peak” amps actually ramping from high speed (6.0 full load amps) up to 10 amps as the motor is slowed down and then as the speed continues to drop down, the amps decreases to approximately 7.2 amps at the lowest speed (which is above FLA and appears to cause the motor to overheat). The Mechanical Field Engineer stated that at the rated full load amps (6.0), the fan CFM was higher than was desired based on the Design Engineer’s parameters. Even though the airflow was above design, the unit was left running at the speed where the motor was operating at full load amps to prevent motor damage. The following table documents the recorded measurements.

ELECTRICAL MEASUREMENTS OF OVEN FAN			
Speed	Amps / Non-Rms	Amps / Rms	Volts At Disconnect
Speed Position As Found	6.96	9.54	123.6
Lowest Speed Position	5.41	7.21	122.3
Highest Speed Position	5.10	6.89	122.5
Speed (Final Setting)	4.56	6.00	123.5



Figure 2. Greenheck CUE 121 Fan - Fan motor with adjustable speed controller.

CONCLUSIONS

A non-true RMS meter will indicate acceptable amperage drawn when the current is actually above the nameplate rating. When measuring current from a variable speed controller, a True RMS meter must be used to obtain consistent correct voltage and amperage measurements. The correlation factors between V_{rms}/A_{rms} and V_{ave}/A_{ave} are neither linear nor constant. This experiment illustrates the linearity between the two meter readings can be close at points, but still not consistent. A true RMS meter should be used by Field Engineers to ensure accurate, consistent, repeatable and safe measurements. The experiment also illustrates that fluctuation of incoming current does affect the output motor via speed controls. This is important because motor/fan speed affects air flow. Without confidence of a stable measurable current both the motor and the air flows are affected. This can lead to improper air flow, heat removal issues and motor damage.

A recommendation was made to consult the fan manufacturer and resolve the electrical issue involving the use of this Vari-Speed controller with the specified motor. In the “as found” condition, the fan should simply be adjusted to a “higher than required” airflow to maintain amperage at or below the nameplate rating. 🌐

References

1. True RMS Definition, application note 106, Linear Technology
2. Fundamental Electrical and Electronic Principle 3rd edition by Christopher R. Robertson, Newness 2008.
3. Fluke Application Notes, Why True-RMS? 2002 Fluke Corporation

ROOT MEAN SQUARE

The RMS value of a set of values (or a continuous-time waveform) is the square root of the arithmetic mean (average) of the squares of the original values (or the square of the function that defines the continuous waveform).

In the case of a set of n values, $\{x_1, x_2, \dots, x_n\}$ the RMS value is given by this formula:

$$x_{rms} = \sqrt{\frac{1}{n} (x_1^2 + x_2^2 + \dots + x_n^2)}$$

The corresponding formula for a continuous function (or waveform) $f(t)$ defined over the interval $T_1 \leq t \leq T_2$ is

$$f_{rms} = \sqrt{\frac{1}{T_2 - T_1} \int_{T_1}^{T_2} [f(t)]^2 dt}$$

And the RMS for a function over all time is:

$$f_{rms} = \lim_{T \rightarrow \infty} \sqrt{\frac{1}{T} \int_0^T [f(t)]^2 dt}$$





COMPARISON OF NON-TRUE RMS AND TRUE RMS METER RESPONSES				
MULTIMETER TYPE	RESPONSE TO SINE WAVE	RESPONSE TO SQUARE WAVE	RESPONSE TO SINGLE PHASE DIODE RECTIFIER	RESPONSE TO 3 PHASE DIODE RECTIFIER
Wave Form				
Average Responding Non-True RMS	Correct	10 % high	40 % low	5-30 % low
True-RMS	Correct	Correct	Correct	Correct

Figure 3. Comparison of Average Responding and True RMS Units. Fluke Application Notes, Why True-RMS? 2002 Fluke Corporation.

AABC Lunch & Learn Presentations *For Engineers*



AABC members are always available to meet with your firm to discuss best practices for testing and balancing. Whether you would like a presentation covering a variety of the most important testing and balancing concepts for engineers, or a more specific topic, let us know and we will arrange for an AABC expert to address your team at no charge!

TOPICS INCLUDE:

- Test & Balance Primer for Engineers
 - Hot Water Reheat Balancing
 - Duct Leakage Testing
 - Control Point Verification
- ...Or Suggest another Topic!



If you would be interested in such a technical presentation, or if you have any other questions or comments, please contact AABC headquarters at headquarters@aacb.com or 202-737-0202.

ALABAMA

Performance Testing & Balancing Co., Inc.
Cleveland, Alabama
(205) 274-4889

Superior Tabs International, Inc.
Pelham, Alabama
(205) 620-2801

Systems Analysis, Inc.
Birmingham, Alabama
(205) 802-7850

ARIZONA

Arizona Air Balance Company
Tempe, Arizona
(480) 966-2001

ETB Arizona, LLC
Glendale, Arizona
(602) 861-1827

General Air Control, Inc.
Tucson, Arizona
(520) 887-8850

Precisionaire of Arizona, Inc.
Phoenix, Arizona
(623) 580-1644

Southwest Testing & Balancing, LLC
Goodyear, Arizona
(602) 370-6601

Systems Commissioning & Testing, Inc.
Tucson, Arizona
(520) 884-4792

Tab Technology, Inc.
Mesa, Arizona
(480) 964-0187

Technical Air Balance SW, Inc.
Phoenix, Arizona
(623) 492-0831

CALIFORNIA

Air Balance Company, Inc.
Diamond Bar, California
(909) 861-5434

American Air Balance Co., Inc.
Anaheim, California
(714) 693-3700

Los Angeles Air Balance Company, Inc.
Upland, California
(800) 429-6880

Matrix Air Balance, Inc.
Torrance, California
(310) 320-9020

MESA3, Inc.
San Jose, California
(408) 928-3000

MESA3, Inc.
Roseville, California
(916) 803-0268

National Air Balance Co., Inc.
Fremont, California
(510) 623-7000

Pacific Test and Balance, Inc.
Napa, CA
(707) 696-2444

Penn Air Control, Inc.
Cypress, California
(714) 220-9091

Penn Air Control, Inc.
Fallbrook, California
(760) 451-2025

Penn Air Control, Inc.
San Jose, California
(510) 509-4005

RSAnalysis, Inc.
El Dorado Hills, California
(916) 358-5672

San Diego Air Balance, Co., Inc.
Escondido, California
(760) 741-5401

Winaire, Inc.
Huntington Beach, California
(714) 901-2747

COLORADO

Proficient Balancing Company, LLC
Arvada, Colorado
(303) 870-0249

CONNECTICUT

CFM Test & Balance Corporation
Bethel, Connecticut
(203) 778-1900

James E. Brennan Company, Inc.
Wallingford, Connecticut
(203) 269-1454

FLORIDA

Air Balance Unlimited, Inc.
Sorrento, Florida
(407) 383-8259

Air Proserv, Inc.
Boca Raton, Florida
(561) 208-3882

Bay to Bay Balancing, Inc.
Lutz, Florida
(813) 971-4545

Bay to Bay Balancing, Inc.
Orlando, Florida
(407) 704-8768

Gregor Hartenhoff, Inc.
Pompano Beach, Florida
(954) 786-3420

Palmetto Air & Water Balance, Inc.
Ft. Myers, Florida
(800) 295-9806

Perfect Balance Inc.
Jupiter, Florida
(561) 575-4919

Precision Balance, Inc.
Orlando, Florida
(407) 876-4112

Southern Balance, Inc.
Milton, Florida
(850) 623-9229

Southern Independent Testing Agency, Inc.
Lutz, Florida
(813) 949-1999

Test and Balance Corporation
Lutz, Florida
(813) 909-8809

The Phoenix Agency, Inc.
Lutz, Florida
(813) 908-7701

Thermocline Corp.
Merritt Island, Florida
(321) 453-3499

GEORGIA

Addison Energy Technologies, LLC
Toccoa, Georgia
(706) 244-0383

Augusta Air Balance Company, LLC
Martinez, Georgia
(706) 799-2254

Southern Balance Company
Marietta, Georgia
(770) 850-1027

TAB Services, Inc.
Norcross, Georgia
(404) 329-1001

Test and Balance Corporation
Roswell, Georgia
(678) 393-9401

GUAM

Penn Air Control, Inc.
Tamuning, Guam
(671) 477-0325

HAWAII

Penn Air Control, Inc.
Aiea, Hawaii
(808) 492-1640

Test and Balance Corp. of the Pacific
Honolulu, Hawaii
(808) 593-1924

ILLINOIS

United Building & Energy Services, LLC
Wheaton, Illinois
(630) 790-4940

INDIANA

Fluid Dynamics, Inc.
Fort Wayne, Indiana
(260) 490-8011

Synergy Test & Balance, Inc.
Indianapolis, Indiana
(317) 222-1828

IOWA

Systems Management & Balancing, Inc.
Waukee, Iowa
(515) 987-2825

KENTUCKY

Thermal Balance, Inc.
Ashland, Kentucky
(606) 325-4832

Thermal Balance, Inc.
Nicholasville, Kentucky
(859) 277-6158

Thermal Balance, Inc.
Paducah, Kentucky
(270) 744-9723

LOUISIANA

Coastal Air Balance Corp.
Metairie, Louisiana
(504) 834-4537

Tech-Test Inc. of Louisiana
Baton Rouge, Louisiana
(225) 752-1664

MARYLAND

American Testing Inc.
Ellicott City, Maryland
(410) 461-6211

Baltimore Air Balance Co.
Bowie, Maryland
(301) 262-2705

Baumgartner, Inc.
Hunt Valley, Maryland
(410) 785-1720

Chesapeake Testing & Balancing Engineers, Inc.
Easton, Maryland
(410) 820-9791

Environmental Balancing Corporation
Clinton, Maryland
(301) 868-6334

Protab, Inc.
Hampstead, Maryland
(410) 935-8249

Test & Balancing, Inc.
Laurel, Maryland
(301) 953-0120

Weisman, Inc.
Towson, Maryland
(410) 296-9070

MASSACHUSETTS

Thomas-Young Associates, Inc.
Marion, Massachusetts
(508) 748-0204

MICHIGAN

Aerodynamics Inspecting Co.
Dearborn, Michigan
(313) 584-7450

Airflow Testing, Inc.
Lincoln Park, Michigan
(313) 382-8378

MINNESOTA

Air Systems Engineering, Inc.
Minnetonka, Minnesota
(952) 807-6744

Mechanical Data Corporation
Bloomington, Minnesota
(952) 473-1176

Mechanical Test and Balance Corporation
Maple Plain, Minnesota
(763) 479-6300

SMB of Minnesota
Blaine, Minnesota
(763) 398-3284

MISSISSIPPI

Capital Air Balance, Inc.
Terry, Mississippi
(601) 878-6701

Coastal Air Balance Corp.
Terry, Mississippi
(228) 392-8768

MISSOURI

Miller Certified Air, Inc.
St. Louis, Missouri
(314) 352-8981

Precisionaire of the Midwest, Inc.
Grain Valley, Missouri
(816) 847-1380

Senco Services Corporation
St. Louis, Missouri
(314) 432-5100

Testing & Balance Co. of the Ozarks, LLC (TABCO)
Ozark, Missouri
(417) 443-4430

NEVADA

American Air Balance Co., Inc.
Las Vegas, Nevada
(702) 255-7331

Mechanical Test and Balance Corporation
Las Vegas, Nevada
(702) 737-3030

Penn Air Control, Inc.
Las Vegas, Nevada
(702) 221-9877

Raglen System Balance, Inc.
Reno, Nevada
(775) 747-0100

RSAnalysis, Inc.
Las Vegas, Nevada
(702) 740-5537

NEW JERSEY

Airology
Bedminster, New Jersey
(908) 722-1776

Effective Air Balance, Inc.
Totowa, New Jersey
(973) 790-6748

National Air Balance Company LLC
Paramus, New Jersey
(201) 444-8777

NEW YORK

Mechanical Testing, Inc.
Waterford, New York
(518) 328-0440

Precision Testing & Balancing, Inc.
Brooklyn, New York
(718) 994-2300

NORTH CAROLINA

Building Environmental Systems Testing, Inc. (BEST, Inc.)
Wilson, North Carolina
(252) 291-5100

e-nTech Independent Testing Services, Inc.
Winston-Salem, North Carolina
(336) 896-0090

Palmetto Air & Water Balance, Inc.
Charlotte, North Carolina
(704) 587-7073

Palmetto Air & Water Balance, Inc.
Greensboro, North Carolina
(336) 275-6678

Palmetto Air & Water Balance, Inc.
Raleigh, North Carolina
(919) 460-7730

Palmetto Air & Water Balance, Inc.
Wilmington, North Carolina
(910) 202-3850

The Phoenix Agency of North Carolina, Inc.
Winston-Salem, NC
(336) 744-1998

NORTH DAKOTA

Design Control, Inc.
Fargo, ND
(701) 237-3037

OHIO

Air Balance Unlimited, Inc.
Gahanna, Ohio
(614) 595-9619

Kahoe Air Balance Company
Cleveland, Ohio
(440) 946-4300

Kahoe Air Balance Company
Liberty Township, Ohio
(513) 248-4141

Kahoe Air Balance Company
Lewis Center, Ohio
(740) 548-7411

PBC, Inc. (Professional Balance Co.)
Willoughby, Ohio
(440) 975-9494

Precision Air Balance Company, Inc.
Cleveland, Ohio
(216) 362-7727

R.H. Cochran and Associates, Inc.
Wickliffe, Ohio
(440) 585-5940

OKLAHOMA

Eagle Test & Balance
Cushing, Oklahoma
(918) 225-1668

OREGON

Northwest Engineering Service, Inc.
Tigard, Oregon
(503) 639-7525

Pacific Coast Air Balancing
Newberg, Oregon
(503) 537-0826

PENNSYLVANIA

Butler Balancing Company, Inc.
Thorndale, Pennsylvania
(610) 873-6905

Flood and Sterling Inc.
New Cumberland, Pennsylvania
(717) 232-0529

Kahoe Air Balance Company
McMurray, Pennsylvania
(724) 941-3335

WAE Balancing, Inc.
Mercer, Pennsylvania
(724) 662-5743

PUERTO RICO

Penn Air Control, Inc.
Naguabo, Puerto Rico
(787) 234-2692

SOUTH CAROLINA

Palmetto Air & Water Balance, Inc.
Greenville, South Carolina
(864) 877-6832

Palmetto Air & Water Balance, Inc.
Charleston, South Carolina
(843) 789-5550

TENNESSEE

Environmental Test & Balance Company
Memphis, Tennessee
(901) 373-9946

Systems Analysis, Inc.
Hermitage, Tennessee
(615) 883-9199

Thermal Balance, Inc.
Nashville, Tennessee
(615) 768-5461

United Testing & Balancing, Inc.
Nashville, Tennessee
(615) 331-1294

United Testing & Balancing, Inc.
Knoxville, Tennessee
(865) 922-5754

TEXAS

Aerodynamics Inspecting Co.
Houston, Texas
(281) 481-2100

Aerodynamics Inspecting of Texas, LLC
Weslaco, Texas
(956) 351-5285

Air Balancing Company, Inc.
Fort Worth, Texas
(817) 572-6994

AIR Engineering and Testing, Inc.
Dallas, Texas
(972) 386-0144

Austin Air Balancing Corporation
Austin, Texas
(512) 477-7247

Delta-T, Ltd.
Garland, Texas
(972) 494-2300

Delta-T, Ltd.
Austin, Texas
(512) 590-1051

Engineered Air Balance Co., Inc.
Richardson, Texas
(972) 818-9000

Engineered Air Balance Co., Inc.
San Antonio, Texas
(210) 736-9494

Engineered Air Balance Co., Inc.
Spring, Texas
(281) 873-7084

National Precisionaire, LLC
Houston, Texas
(281) 449-0961

Online Air Balancing Company
Houston, Texas
(713) 453-5497

PHI Service Agency, Inc.
San Antonio, Texas
(210) 224-1665

PHI Service Agency, Inc.
Austin, Texas
(512) 339-4757

PHI Service Agency, Inc.
Alamo, Texas
(956) 781-9998

PHI Service Agency, Inc.
Corpus Christi, Texas
(361) 248-4861

Professional Balancing Services, Inc.
Dallas, Texas
(214) 349-4644

TAB Solutions, Inc.
Lakeway, Texas
(720) 220-1062

Technical Air Balance, Texas
Spring, Texas
(281) 651-1844

Texas Test & Balance
Houston, Texas
(281) 358-2118

UTAH

Mechanical Testing Corporation
Leeds, Utah
(435) 879-8714

RSAnalysis, Inc.
Sandy, Utah
(801) 255-5015

VIRGINIA

Arian Tab Services
Herndon, Virginia
(703) 319-1000

C&W-TESCO, Inc.
Richmond, Virginia
(804) 379-9345

Mid-Atlantic Test & Balance, Inc.
South Boston, Virginia
(434) 572-4025

WASHINGTON

Eagle Test & Balance
Bellevue, Washington
(425) 747-9256

TAC Services, LLC
Bellingham, Washington
(360) 224-8555

WISCONSIN

Professional System Analysis, Inc.
Germantown, Wisconsin
(262) 253-4146

MANITOBA

A.H.S. Testing & Balancing Ltd.
Winnipeg, Manitoba
(204) 224-1416

Air Movement Services Ltd.
Winnipeg, Manitoba
(204) 233-7456

AIRDRONICS, Inc.
Winnipeg, Manitoba
(204) 253-6647

D.F.C. Mechanical Testing & Balancing Ltd.
Winnipeg, Manitoba
(204) 694-4901

NEW BRUNSWICK

Controlled Air Management Ltd.
Moncton, New Brunswick
(506) 852-3529

Scan Air Balance 1998 Ltd.
Moncton, New Brunswick
(506) 857-9100

Source Management Limited
Fredericton, New Brunswick
(506) 443-9803

NOVA SCOTIA

Griffin Air Balance Ltd.
Dartmouth, Nova Scotia
(902) 434-1084

Scotia Air Balance 1996 Limited
Antigonish Co., Nova Scotia
(902) 232-2491

ONTARIO

Accu-Air Balance Co. (1991) Inc.
Windsor, Ontario
(519) 256-4543

Air & Water Precision Balancing, Inc.
Toronto, Ontario
(647) 896-5353

Airwaso Canada Inc.
London, Ontario
(519) 652-4040

Caltab Air Balance Inc.
Tecumseh, Ontario
(519) 259-1581

Designtest & Balance Co. Ltd.
Richmond Hill, Ontario
(905) 886-6513

Dynamic Flow Balancing Ltd.
Oakville, Ontario
(905) 338-0808

Kanata Air Balancing & Engineering Services
Ottawa, Ontario
(613) 832-4884

Pro-Air Testing Inc.
Toronto, Ontario
(416) 252-3232

Vital-Canada Group Inc.
Mississauga, Ontario
(905) 848-1000

VPG Associates Limited
King City, Ontario
(905) 833-4334

AABC INTERNATIONAL MEMBERS

SOUTH KOREA

Awin ENC Co., Ltd.
Soengdong-gu, Seoul
SOUTH KOREA
+82-2-2117-0290

Energy 2000 Technical Engineering Co., Ltd.
Songpa-gu, Seoul
SOUTH KOREA
+82-2-408-2114

KYUNGMIN FNE
Gangbuk-gu, Seoul
SOUTH KOREA
+82-2-7077-9447-33

Penn Air Control, Inc.
Gangbuk-gu, Seoul
SOUTH KOREA
+82-2-982-0431

ITALY

Studio S.C.S. Ingegneri
Scarbaci-Cuomo
Pordenone, ITALY
+39-0434-29661



Have an Opinion?

**An interesting case study?
A new method? Tell us about it.**

TAB Journal welcomes submissions for publication. TAB Journal is published quarterly by the Associated Air Balance Council. Send letters or articles to:

*Editor • TAB Journal
1518 K Street, NW, Suite 503
Washington, DC 20005 • info@aaabc.com*

ACCURATE. DEPENDABLE. VERSATILE.

Only TSI-Alnor EBT731 Balometer® Capture Hood can:

- + Provide most accurate measurement
- + Enable easy, efficient one-person operation
- + Offer innovative accessory choices

New Added Features and Accessories Include:

- + Detachable auto-zeroing micromanometer with duct traverse mapping application
- + Accessory probe options (pitot, thermoanemometer, temperature and humidity)
- + Remote display and logging via LogDat™ Mobile Android™ Software
- + Labor-saving capture hood stand

There's never been a better time to buy—Bundle and Save:

BUNDLE WITH TSI & SAVE
A savings of \$365 then if purchased separately

Model	Bundle Contents
EBT731-STA	+ EBT731 Balometer Capture Hood + Capture Hood Stand + Smart Tablet* loaded with LogDat™ Mobile App and Instruction Videos

Choose the EBT731 Balometer to drive your efficiency and performance while increasing revenue.

www.tsi.com/ebt731

 Designed and assembled in America

*TSI has the discretion to change the brand and model of tablet at any time.

