

# TAB Journal

THE MAGAZINE OF THE ASSOCIATED AIR BALANCE COUNCIL • SUMMER 2016



## *New Developments in* **Hydronic Systems**

### ALSO IN THIS ISSUE:

- Buoyancy Driven Ventilation Systems
- Drywall Chases
- Jobsite Safety




# 7th Edition of the AABC National Standards *Now Available!*



**Order your  
copy of the  
AABC National  
Standards for  
Total System  
Balance today!**

[www.AABC.com/publications](http://www.AABC.com/publications)



## **A MUST-HAVE RESOURCE FOR HVAC ENGINEERS!**

This comprehensive manual for the test and balance industry details the minimum standards for total system balance, assists design professionals in achieving design intent, provides a better understanding of the scope of work required of the TAB agency, and ensures that proper methods and procedures are followed in the test and balance process.

For the first time, this newest edition is American National Standards Institute (ANSI) approved.

### **New, additional and revised content includes:**

- All-new sections on testing energy recovery systems and chilled beams
- Revised and updated content on constant volume air systems
- Revised recommendations for duct leakage testing
- Recommendations for air handling unit pressure testing including deflection testing
- New chapter on "Testing and Balancing Health Care Facilities"
- Updated testing tolerances for air, hydronic, pressure and temperature
- Expanded chapters on hydronic balancing and new chapter on domestic water balancing
- Recommendations for room, floor and building pressure testing
- Important updates to laboratory and kitchen systems.

Order the new edition of the  
AABC National Standards online at  
[www.AABC.com/publications](http://www.AABC.com/publications)



**Associated Air Balance Council**

1518 K Street, N.W., Suite 503  
Washington, D.C. 20005 • 202-737-0202



# TAB Journal

## Associated Air Balance Council BOARD OF DIRECTORS AND OFFICERS

### President

Daniel J. Aciri  
*Flood and Sterling Inc.*

### Executive Vice President

Michael L. Delcamp  
*National Precisionaire, LLC*

### Secretary/Treasurer

Benjiman J. Link  
*United Testing & Balancing, Inc.*

### Vice President/Eastern Zone-1

Michael S. Kelly  
*American Testing Inc.*

### Vice President/Central Zone-2

Douglas R. Meacham  
*Kahoe Air Balance Company*

### Vice President/Western Zone-3

Gaylon Richardson  
*Engineered Air Balance Co. Inc.*

### Immediate Past President

Jay A. Johnson  
*Thermal Balance, Inc.*

### Director, Canadian Chapter

Donald F. C. Mowat  
*D. F. C. Mechanical Testing & Balancing Ltd.*

### Executive Director

Kenneth M. Sufka

### Editorial Director

Ray Bert

### TAB Journal Editor

Ashley Weber

### Technical Advisor

Joseph E. Baumgartner, III, P.E.

### Editorial Office

1518 K Street, N.W., Suite 503  
Washington, D.C. 20005  
(202) 737-0202 • FAX: (202) 638-4833  
E-mail: [info@aabc.com](mailto:info@aabc.com)  
Website: [www.aabc.com](http://www.aabc.com)

*TAB Journal* is published quarterly by the Associated Air Balance Council. It is distributed free to AABC members and by subscription to non-members at \$24 per year. *TAB Journal* is an open forum for the free expression of opinions and information. The views expressed are not necessarily those of AABC, its officers, directors, or staff. Letters, manuscripts, and other submissions are welcome. However, *TAB Journal* accepts no responsibility for unsolicited material. All rights reserved. Copyright © 2016 by the Associated Air Balance Council.

## TAB INTERACTIVE



Scan this code to  
view the *TAB Journal*  
online archives.

## ECO BOX

*TAB Journal* magazine text and cover pages are printed on SFI®-certified Creator Gloss paper using soy ink.



SFI standards conserve biodiversity and protect soil and water quality, as well as wildlife habitats.

The SFI certified sourcing label is proof AABC is using fiber from responsible and legal sources.

SFI participants also plant more than 650 million trees each year to keep these forests thriving.

## Buoyancy Driven Ventilation Systems ..... 2

Sean Bunting, TBE

*National Air Balance Company, Inc.*

## The Care and Feeding of Sensorless Pump Control ..... 6

Andy J. Cripe, TBE

*Aerodynamics Inspecting of Texas, LLC*

## Drywall Chases – Problematic Observation ..... 12

Harry E. Gaines, TBE

*Testing & Balancing Co. of the Ozarks, LLC (TABCO)*

## Jobsite Safety and OSHA Regulations ..... 14

David W. Miller, TBE

*Miller Certified Air, Inc.*

## Tech Tips: Wild Voltage Leg..... 16

Dean Steffen, TBE

*Precisionaire of Arizona, Inc.*

## Flow Measurement Taps in a Variable Volume Box ..... 18

Surrinder Sahota, TBS

*Designtest & Balance Co. Ltd.*

# From the Publisher

The Summer 2016 issue of *TAB Journal* looks at new developments in hydronic systems with Andy J. Cripe of Aerodynamics Inspecting of Texas, LLC, discussing “sensorless” pump control.


Also in this issue, Sean Bunting, TBE, of National Air Balance Company looks at a the testing procedures for Buoyancy Driven Ventilation Systems.

Harry E. Gaines, TBE, of Testing & Balancing Co. of the Ozarks, LLC, details a case study in which exhaust problems required investigation at a hotel, and leakage was discovered inside the drywall chases.

David W. Miller, TBE, of Miller Certified Air, Inc., stresses the importance of proper jobsite safety training.

In this issue’s Tech Tip, Dean Steffen, TBE, of Precisionaire of Arizona, Inc., looks at voltage variations that can occur on balancing projects and how to resolve them.

And finally, Surrinder Sahota, TBS, of Designtest & Balance Co., Ltd., discusses why flow measurement taps are needed in variable volume boxes.

We would like to thank all of the authors for their contributions to this issue of *TAB Journal*. Please contact us with any comments, article suggestions, or questions to be addressed in a future Tech Talk. We look forward to hearing from you! 





# BUOYANCY DRIVEN VENTILATION SYSTEMS

By Sean Bunting, TBE  
National Air Balance Company, Inc.

**N**ational Air Balance Company, Inc. was recently asked by a local Mechanical Engineer of Record (MEOR) to review their TAB specification for a “Buoyancy Driven Natural Ventilation System”, and what was found was concerning. Their specification called for very little testing, adjusting and balancing (TAB) to be performed. This issue was discussed with them, with reasons pointed out why a more extensive TAB process was required.

## **System Operation Overview:**

- The, “Buoyancy Driven Ventilation System” is designed to induce air across a Chilled Water (CHW) or Heating Water (HHW) coil to maintain room temperature of a space without the use of any mechanical HVAC equipment to move the air. This is done using Outside Air (OSA) dampers that modulate based on wind speed and the CHW/HHW valve position for the associated coils.

*Below is the procedure that was established for testing the Buoyancy Driven Ventilation System.*

## **Inspections to be made prior to beginning the associated testing:**

- Visually inspect the building to ensure it is architecturally complete. This includes doors (interior/exterior), glass (interior exterior/envelope), ceilings, etc.
- Confirm all architectural shafts are complete.

## **Prerequisites to testing the Buoyancy Driven Ventilation System:**

- Controls check out confirmed successfully complete with all design parameters programmed into the Building Management System (BMS).
- CHW/HHW systems are operating in automatic and controlling at their design temperatures.





- Outside Air (OSA)/Relief Air dampers are operating correctly.
- Under Floor Automatic Control Dampers (ACD's) and Air Monitoring Stations (AMS') are operating correctly and have been successfully calibrated.
- Wind Speed and Directional Transmitters are operating correctly and have been successfully calibrated.
- All other HVAC systems have been successfully balanced.

#### **Conditions to be maintained during testing of the Buoyancy Driven Ventilation Systems:**

- Supply Air (SA), Return Air (RA) and Toilet Exhaust Air (EA) systems operating in their normal modes.
- All doors and windows must be in their normal positions (open/closed).
- Occupants' foot traffic to be managed and kept to a minimum.

#### **Testing Procedure of the Buoyancy Driven Ventilation System:**

- Read and record the velocity across the CHW coil at the top of the intake shaft.
- Read and record the velocity at each ACD/AMS at the intakes to each room (interior/perimeter zones).
- Read and record the velocity of the Relief Air through each damper at the top of the Atrium.
- Read and record the velocity at each Transfer Ducts related to the Buoyancy System (shown on M-212A, B).
- Read and record system static pressures and plenum differential pressures.
- Record intake damper positions.



- Read and record wind speed and direction (to be measured during balance).
- Read and record OSA flow rates in full cooling mode. This will be done one shaft at-a-time. After all shafts are completed, all other modes will be trended for 48 hours. Trend data will be reviewed with the MEOR to determine if further testing is required.
- Read and record entering and leaving air temperatures.
- Read and record Relative Humidity (RH) at the cooling coils.
- Read and record temperature and RH at each ACD, interior spaces and OSA.
- Install filter media upstream of each cooling coil imposing a pressure drop of 0.1" WG. Trend the AMS and temperatures for 48 hours.
- Document the airflow rate of each air outlet in the

raised floor by using the manufacturer's flow charts.

- Read and record building pressurization.

From the points listed above, the procedure is extensive. But as originally specified, much of this testing would not have been required. This is why it is imperative TAB contractors stay actively involved with their local mechanical engineering community, so that as the HVAC industry evolves with newer more sophisticated systems, the TAB industry remains relevant.

When reviewing a TAB specification and deficiencies are noticed and/or key elements are not listed, reach out to the MEOR to discuss what testing should be added to ensure their design intent is met. 🌐

**Transparent window for ease of use**

**Bluetooth communication to tablet**

## ***TABmaster™ Model 6715*** Airflow Capture Hood

Micromanometer function with Bluetooth® wireless communication with Android device



**KANOMAX**  
The Ultimate Measurements

**Kanomax USA, Inc.**  
info@kanomax-usa.com  
URL: www.kanomax-usa.com

Watch a video!





We measure it.



# Light weight and Rugged

## We make air flow testing a *breeze*

Testo has a complete line of air flow instruments for your every need. We offer compact Smart Probes that work wirelessly with a smart phone, and we have multi-probe instruments for IAQ parameters. Also available is the **new** testo 420 Flow hood with built-in flow straighteners, Bluetooth communications for remote measurements, and wireless data reporting.



With Testo app  
operation via  
Bluetooth:

testo 420 / testo Smart Probes



Testo is an ISO 17025 certified NIST laboratory,  
for all your calibration needs!



[www.testo.com/air-flow](http://www.testo.com/air-flow)




# THE CARE AND FEEDING OF **SENSORLESS PUMP CONTROL**

**Andy J. Cripe, TBE**

*Aerodynamics Inspecting of Texas, LLC*




A recent development in hydronic systems has been the emergence of “sensorless” pump control, offered by several manufacturers. Sensorless pump control typically consists of a pump packaged with a pump-mounted VFD (Variable Speed Drive), supplied and programmed by the manufacturer, offering variable-speed control of the pump without the need of a downstream differential pressure transducer.



## PUMP PERFORMANCE CURVE

This is the pump curve for that pump with the operating point shown:



With the operating point located on the pump curve, it is apparent that the impeller is oversized for the application, which means the pump submitted will reach the design operating point at something less than full speed or 60 Hz at about 48 HP, nearly full load for the motor.


The premise of sensorless pump control is that based on a given pump, impeller and a system curve, the VFD can calculate pump flow at any speed based on pump power consumption and can use this to keep the pump operating on the system curve. The challenge for the Test and Balance industry is how to deal with these animals so they function reliably and as-intended.

### Pump Curves

Hydronic balancing (after system control valves are opened to their design flow configuration) begins with setting the flow at the pump by measuring the pump shut-off head and using that figure to determine the pump impeller size. Once impeller size is known, the manufacturer's pump curve allows us to determine flow based on the pump head.



## PUMP PERFORMANCE ENVELOPE CURVE



Meanwhile, the pump curve in the equipment submittal looks like this (also with the operating point added). While somewhat informative, the performance envelope curve is not much help in balancing the pump. It shows that the pump selected is capable of performing at design and it can operate down to about 70% of design load. It does not show RPM or impeller sizes.

Using a recent middle-school project as an example, the installed secondary pumps were Armstrong 4300IVS-8 0408-050.0 which translates as a 4800 series pump 4x4x8 (3600 RPM) with a 50 HP motor. The pump is rated for 1065 GPM at 135 ft. head with a 7.11 in. impeller.

The premise of the sensorless pump technology is that for a given pump and impeller size and a given system curve, there is a unique pump head and flow for each combination of pump speed and power input. With a system curve defined, the pump VFD can calculate pump head and flow at any operating point and uses pump speed control to stay on the system curve. This replicates variable speed control with a downstream differential pressure transmitter

installed without requiring its actual installation. Settings are also available for maintaining constant flow or constant head.


### Balancing Sensorless Pumps

For the purposes of this example, Armstrong IVS pumps will be used. IVS Sensorless pumps generally ship with the design system curve loaded into the VFD; however the curve is just the engineer's best guess at system head and is usually on the conservative side. This will result in pump speeds higher than necessary and added pump energy consumption, the same as a conventional system with the differential pressure setpoint set too high. Calibrating the setup requires determining the actual

## SENSORLESS PUMP PERFORMANCE CURVE

The operating curve for a sensorless pump application takes the standard performance curve and turns it on its ear. Instead of pump speed being constant and pump impeller size and pump head variable, the pump impeller size is constant and pump speed and head are variable. This is an example of just such a curve (though it is based on an 1800-RPM motor instead of the 3600-RPM examples above):

The green line on the pump curve is the system curve. It starts at the rated flow and head, in this case 525 GPM at 55 ft., and assumes the system reaches no-flow conditions at a default 40% of the design head. In this case, pump speed would be at max at the rated design flow; however, design pump speed is often less than 100% for a given application.



head required to meet design flow under design cooling conditions.

Typically, the only pump curves available to the test and balance crew on a project are the standard curve with the pump at full speed, showing the range of impeller sizes. The pump may not be programmed to run at full speed, so a jumper needs to be installed to bring the VFD up to 60 Hz. This is taken from an Armstrong brochure for IVS sensorless pumps:

Adding a jumper between terminals 39 and 42 will bring the VFD to 60 Hz. With the pump at full speed, use the pump discharge valve to throttle flow to design, then measure system pressure somewhere downstream of the discharge valve. If no ports are

available downstream of the discharge valve, check pressure drop across a coil. Open the discharge valve and reduce pump speed manually until the pressure drop matches the earlier pressure drop. This will have the pump at design flow and at the head required to match that flow.


These are the parameters used in the VFD's for sensorless pump operation for the Armstrong IVS pumps:

Parameter 20-21 is the key parameter used to adjust pump settings from the scheduled head for the pump to the actual head. With that parameter adjusted, system flow should be at design with chilled water valves calling for full cooling (accounting for any



## CONSTANT CURVE MODE - BMS SIGNAL

It may be requires to run the pump at full speed without automatic speed control (eg. during system commissioning.) This can be achieved without programming changes by making the connections below.



## VFD PARAMETERS FOR ARMSTRONG IVS SENSORLESS PUMPS:

It may be requires to run the pump at full speed without automatic speed control (eg. during system commissioning.) This can be achieved without programming changes by making the connections below.


|                       |                                   |                                 |
|-----------------------|-----------------------------------|---------------------------------|
| DRIVE CLOSED LOOP     | 20-00 Feedback 1 source           | Sensorless pressure             |
|                       | 20-02 Feedback 1 source unit      | Unit used for feedback 1 source |
|                       | 20-12 Reference/feedback unit     | Unit of par 2021 (ex: ft wg)    |
|                       | 20-13 Minimum reference/feedb.    |                                 |
|                       | 20-14 Maximum reference/feedb.    | Max of head and flow mapped     |
|                       | 20-20 Feedback function           | Minimum                         |
|                       | 20-21 Setpoint 1                  | Design head in unit in par 2012 |
|                       | 20-60 Sensorless unit             | Unit of par 1850 (ex: gpm)      |
|                       | 20-70 Closed-loop type            | Not used                        |
|                       | 20-71 pid performance             | Not used                        |
|                       | 20-93 pid proportional gain       | Start at 0.05                   |
|                       | 20-94 pid integral time           | Start at 0.1                    |
| APPLICATION FUNCTIONS | 22-43 Wake up speed [Hz]          | Not used                        |
|                       | 22-50 End of curve function       | Off                             |
|                       | 22-80 Flow compensation           | [1] Enabled                     |
|                       | 22-81 Square-linear curve approx. | 100%                            |
|                       | 22-84 Speed at no-flow [Hz]       | Not used                        |
|                       | 22-86 Speed at design point [Hz]  | Not used                        |
|                       | 22-87 Pressure at no-flow speed   | 40% of maximum system head      |
|                       | 22-89 Flow at design point        | Flow at design point            |

diversity in the system). The pump should then operate satisfactorily, providing variable speed control in sensorless mode.

This same routine should work well with other makes of sensorless pumps as well.

- Drive the pump to full speed.
- Throttle the pump to design flow using the pump curve.
- Measure system pressure downstream of discharge valve.

- Open discharge valve and reduce pump speed to get back to design flow.
- Adjust design head parameter at the VFD to measured pump head.

Sensorless pump applications will probably become more and more common with time. With the proper setup and balancing, they will perform satisfactorily. 

*Reference: Armstrong Design Envelope 4300 Pumps - I&O*

REGISTER NOW

free for a limited time

# EXPERIENCE THE FUTURE OF HVACR

- SEE NEW PRODUCTS FROM 2,000+ EXHIBITORS
- NETWORK WITH 60,000+ HVACR PROFESSIONALS
- ATTEND SEMINARS & ASHRAE WINTER CONFERENCE



**AHR  
EXPO®**

LAS VEGAS **JAN 30-FEB 1** 2017

CO-SPONSORS



**AHREXPO.COM**





# Drywall Chases

## Problematic Observation

Harry E. Gaines, TBE

Testing & Balancing Co. of the Ozarks, LLC (TABCO)



**A** Springfield, Missouri hotel management and ownership company reached out to inquire as to whether exhaust problems could be investigated that they were having at one of their newer resort hotels that they owned in another state. A meeting was planned at their local office to discuss the particular concerns with this facility and to review the original testing and balancing report submitted for this project.

Review of the test and balance report revealed that the exhaust fans serving the (120) guest rooms were not delivering the design CFM required for each bathroom inlet. It was also determined that the direct drive exhaust fans were running at maximum speed which, according to the design requirements, was not required in order to achieve the design CFM. The owners were questioned to see if their perceived


problem was low airflow at the inlets or if the building was drawing in outside air at the entrances to the building. Their response was that they believed both to be true and that there was a whistling noise when the doors were closed.

It was requested during the meeting that we would accompany their head maintenance person to the hotel to check the conditions and report back the findings.

During the visit to this hotel, it was decided that (2) bathroom exhaust fans would be tested at random. For discussion purposes, these (2) tested fans will be called EF-A and EF-B. The following information was tabulated from the testing:

It was obvious from the original TAB report that there was a problem with the leakage inside the drywall chases which





“... a request was made during the construction phase by the general contractor to expedite this part of the construction with drywall chases for the bathroom exhaust.”

were constructed to carry the bathroom exhaust out of the building by way of the exhaust fans located on the roof above the fourth floor. It is worth noting that it was during the construction phase that a request was made by the general contractor to expedite this part of the construction by constructing these drywall chases to carry the bathroom exhaust. This was signed off on by both the architect and the mechanical engineer. No testing of the drywall chases was done to demonstrate integrity of the chases.

EF-A design for the (4) bathrooms was 180 CFM. The inlets were read and totaled at 123 CFM. A traverse at the roof read 333 CFM. This shows that there was 210 CFM of leakage occurring.


EF-B design CFM for (8) bathrooms was 360. The inlets again were read and totaled 304 CFM. The traverse at the roof read 771 CFM. This shows that there was 467 CFM of leakage into the chase serving EF-B. Both fans were running at their maximum RPM of 1725.

At this point, their head maintenance person suggested an inspection of the drywall wall chases from inside the chase from the roof and outside the chase itself from one of the bathroom ceilings. A hole was cut next to the chase for EF-B in the ceiling of the bathroom on the fourth floor and a high intensity spotlight was pointed at the chase. Upon going to the roof and removing EF-B from the roof curb, an extreme amount of light could be seen pouring from where the drywall

met the roof pan which looked to be sealed with fire caulk.

It was concluded that this similar scenario would be found throughout the other drywall chases in the entire building. This information was reported to the owners and the recommendation was made that each bathroom have its own exhaust fan installed that would be controlled by a light switch and that the exhaust fans on the roof be set to design CFM. The best recommendation would be to seal the chases but due to their 14x14 size, it would be impossible to seal the chases from the outside which would require removal of drywall ceiling and walls in all (120) bathrooms.

In conclusion, a poor choice was made during construction to eliminate ductwork inside the drywall chases causing the exhaust system to perform poorly, producing other unintended consequences. It is recommended that drywall duct chases should never be used for supply or exhaust due to leakage and the possibility of mold growth within a moisture-laden environment.

This is just another example of the value of early testing and balancing professional recommendations in lieu of “under pressure decisions” made to expedite a project which often includes eliminating testing and balancing altogether when project budgets overrun and general contractors and construction managers are searching for ways to bring the project budgets back in line and the job delivered in the timeline promised. 



# Jobsite Safety and **OSHA Regulations**

David W. Miller, TBE  
Miller Certified Air, Inc.




**J**obsite safety has always been a necessity for those working in the testing and balancing industry. On a typical project technicians work with numerous ladders, electrical components, rotating machinery, high temperature fluids and occasionally hazardous chemicals. OSHA regulations require that a minimum understanding of basic safety procedures be demonstrated in every aspect of construction.

In an area of the country where nearly all construction is performed by union craftsman, the Associated General Contractors (AGC), as well as specific trade unions, offer and require safety training of all personnel working in the field. Field technicians can attend 40-hour comprehensive training programs and technical office staff can attend a 10-hour OSHA program. The Associated and Builders and Contractors, Inc. (ABC) also offer training programs to meet OSHA regulations.

The OSHA Standards for the Construction Industry is a comprehensive book that details all of their requirements. It also describes the fines for infractions of those requirements. While a large portion is devoted to activities that would not normally be required of a TAB technician, it is wise to at least be aware of their existence. The AGC and ABC training programs offer an effective way for becoming familiar with jobsite practices. The training programs also covers safety





information for the proper use of ladders, tying off and safety procedures to be followed while working with electrical systems. This is extremely valuable information that all should be aware of and practice every day.

Technicians can benefit from enrolling in one of the AGC or ABC programs which are available throughout the country. The time required is well spent if only one accident can be prevented. 🌐

The OSHA Standards for the Construction Industry is a comprehensive book that details all of their requirements. It also describes the fines for infractions of those requirements.

## Need a Better Test & Balance Spec? AABC CAN HELP!

- Specify for Independence
- Detailed contractor responsibilities to ensure system readiness for T&B
- Recommended, achievable tolerances
- Detailed procedural requirements
- AIA format, MasterSpec approved



For more information: [www.aabc.com/specs](http://www.aabc.com/specs)  
Email [headquarters@aabc.com](mailto:headquarters@aabc.com), or call 202-737-0202





# Techtips

## Wild Voltage Leg


Dean Steffen, TBE, Precisionaire of Arizona, Inc.

On a lot of our remote testing and balancing projects problems are encountered with voltage variations between the three phases. Electricians call it a wild leg on the line voltage. It is usually within tolerance of the equipment it is operating, but can vary as much as 10-12%. This may cause an amperage draw problem when trying to load the fan close to nameplate amps.

One recent incident involved increasing a MUA unit to nameplate amps of 5.2 to achieve as much air as possible. The amp draw went to 5.0/5.1/5.9. This was unacceptable to the engineer. By rolling the phases, L-1 to L-2, L-2 to L-3, and L-3 to L-1, it was possible to even out the amp draw to 5.1/5.4/5.1 without changing rotation on the fan. This does not always work, but for the short amount of time it takes, it is well worth a try. 🌐

Do you have a  
“Tech Tip” that you  
would like to share  
with our readers?  
If so, please  
contact AABC at:


**Associated Air  
Balance Council**  
1518 K Street NW, Ste 503  
Washington, DC 20005  
Fax 202.638.4833  
E-mail: [info@aaabc.com](mailto:info@aaabc.com)  
[www.aabc.com](http://www.aabc.com)



# TABPRO

## TRAINING SERIES

**Save 10% when you order all three TABpro DVDs!**  
You'll get lessons on standard VAVs, parallel fan-powered VAVs, standard duct leakage testing, pressure decay leakage testing, and basic psychrometrics.



**Bundle (VAV, Duct Leakage & Psychrometrics)**

**3 DVDs**

Total run time 106 minutes

List price: \$468.00

Member price: \$351.00



### Basic Psychrometrics

DVD format  
Run time: 19 minutes  
List price: \$120.00  
Member price: \$90.00

This volume contains one lesson on basic psychrometrics. This provides the viewer with an introduction to psychrometric fundamentals and takes you through five of the basic elements found on the psychrometric chart. This lesson will break down these elements on the chart and provide fundamental concepts of chart usage.

### Duct Leakage and Pressure Decay Testing

DVD format  
Run time: 42 minutes  
List price: \$200.00  
Member price: \$150.00

This volume consists of two lessons covering standard duct leakage testing and pressure decay leakage testing. These lessons take the viewer through an introduction to leakage testing, essential job preparation, instrumentation used during testing, general procedures for leakage testing, multiple calculations used during testing and final reporting.

### Variable Air Volume (VAV) Terminals

DVD format  
Run time: 45 minutes  
List price: \$200.00  
Member price: \$150.00

This volume consists of two lessons covering standard VAVs and parallel fan-powered VAVs, both using DDC controls. These lessons take the viewer through an introduction to VAV terminals, essential job preparation, instrumentation used during testing, general procedures for testing and balancing, and final reporting.

| Quantity | Title                | Price      |        |
|----------|----------------------|------------|--------|
|          |                      | Non-Member | Member |
| _____    | Psychrometrics       | \$120      | \$90   |
| _____    | Duct Leakage         | \$200      | \$150  |
| _____    | VAV Terminals        | \$200      | \$150  |
| _____    | Bundle of all 3 DVDs | \$468      | \$351  |

Total: \$ \_\_\_\_\_

#### Payment Information

Payment Type (Check one)

☐ Check Enclosed ☐ MC ☐ Visa ☐ AMEX

Card Number \_\_\_\_\_

Expiration Date \_\_\_\_\_

Name on Card \_\_\_\_\_

Signature \_\_\_\_\_

#### Please complete order form and return along with payment to:

Associated Air Balance Council  
1518 K Street, N.W., Suite 503  
Washington, D.C. 20005

Credit card purchasers may fax orders to: (202) 638-4833 or order online at [www.aabc.com/publications](http://www.aabc.com/publications)

#### Shipping Information

Name \_\_\_\_\_

Phone \_\_\_\_\_

Company \_\_\_\_\_

Fax \_\_\_\_\_

Shipping Address \_\_\_\_\_

E-mail \_\_\_\_\_


City/State/Zip \_\_\_\_\_



# FLOW MEASUREMENT TAPS IN A VARIABLE VOLUME BOX

**Surrinder Sahota, TBS**


*Designtest & Balance Co. Ltd.*



**E**ach variable box or fan-powered box has a flow measurement tap which is connected from the measuring grid to the controller. The measuring grid has multiple measuring points and sends the average velocity pressure to the controller. The manufacturer marks high and low on the outside of the box. High is the total pressure and low is the static pressure. When connected to the controllers, the controller maintains the difference of high and low which is velocity pressure.

The air balancing technician connects to the high and low tap and adjusts the controller to the required velocity pressure and converts to CFM by looking at the chart provided by the manufacturer. Accuracy can be verified with inlet traverses.

Once design CFMs are adjusted, the technician can balance the outlets downstream of each box. On fan-powered boxes, the air balancing technician sets the primary air by measuring the velocity pressure and converting to the CFM. Total air is adjusted from the speed controller.

Most of the variable volume boxes and fan powered boxes are DDC with the technology change. Some air balancing technicians are starting to take the CFM from the computer readout and informing the manufacturer that they can read and calibrate the CFM from the computer readout. Some manufacturers have stopped installation of taps, their claim being that some balancers say they do not need them. 

## Here are some reasons flow measurement taps are needed:

1. Verification of airflow at the box vs. flow at the outlets; the correction factor for the flow hood or other velocity meter can be determined because the grid inside the box is a multi-point traverse station which can also be verified by an inlet traverse
2. Verification of third party. When a consultant engineer or a commissioning agent wants to spot check the readings it needs to be verified that the VAV box air volume has not changed since the balancing was done. It could be difficult to convince a third party that the balancing report is accurate without being able to actually measure the controller velocity pressure.
3. Helpful to the building staff to verify the flow when they get a complaint. All they need is to measure the velocity pressure and compare with the certified report.
4. Balancing technician's instrument is more accurate than the transducer supplied by the box manufacturer. Transducers can go out of calibration after a while and air volume will change but if taps are available, the velocity pressure can be verified and recalibrated by adjusting the K factor.
5. When duct distribution downstream of the VAV box is above the solid ceiling and measured flow is in doubt. The flow can be measured by connecting to the taps to find out if there is any opening left in the duct or some broken duct joints. When using the velocity pressure vs. CFM on DDC system, care must be taken because some transducers have airflow going through from high to low but most of them do not have flow going through. When flow through transducers are used, measured velocity pressure can be used for reference only. Each size VAV box must be traversed, and CFM calculated from the duct traverse should be compared with the box manufacturer. If airflow measured by the duct traverse does not match, either call the manufacturer for an updated chart or use a correction factor to determine most accurate measurements.

## AABC Lunch & Learn Presentations *For Engineers*



AABC members are always available to meet with your firm to discuss best practices for testing and balancing. Whether you would like a presentation covering a variety of the most important testing and balancing concepts for engineers, or a more specific topic, let us know and we will arrange for an AABC expert to address your team at no charge!

### TOPICS INCLUDE:

- Test & Balance Primer for Engineers
  - Hot Water Reheat Balancing
  - Duct Leakage Testing
  - Control Point Verification
- ...Or Suggest another Topic!*



If you would be interested in such a technical presentation, or if you have any other questions or comments, please contact AABC headquarters at [headquarters@aabc.com](mailto:headquarters@aabc.com) or 202-737-0202.



## ALABAMA

Performance Testing & Balancing Co., Inc.  
Cleveland, Alabama  
(205) 274-4889

Superior Tabs International, Inc.  
Pelham, Alabama  
(205) 620-2801

Systems Analysis, Inc.  
Birmingham, Alabama  
(205) 802-7850

## ARIZONA

Arizona Air Balance Company  
Tempe, Arizona  
(480) 966-2001

ETB Arizona LLC  
Glendale, Arizona  
(602) 861-1827

General Air Control, Inc.  
Tucson, Arizona  
(520) 887-8850

Precisionaire of Arizona, Inc.  
Phoenix, Arizona  
(623) 580-1644

Southwest Testing & Balancing, LLC  
Goodyear, Arizona  
(602) 370-6601

Systems Commissioning & Testing, Inc.  
Tucson, Arizona  
(520) 884-4792

Tab Technology, Inc.  
Mesa, Arizona  
(480) 964-0187

Technical Air Balance SW, Inc.  
Phoenix, Arizona  
(623) 492-0831

## CALIFORNIA

Air Balance Company, Inc.  
Covina, California  
(626) 339-4700

American Air Balance Co., Inc.  
Anaheim, California  
(714) 693-3700

Los Angeles Air Balance Company, Inc.  
Upland, California  
(800) 429-6880

Matrix Air Balance, Inc.  
Torrance, California  
(310) 320-9020

MESA3, Inc.  
San Jose, California  
(408) 928-3000

MESA3, Inc.  
Roseville, California  
(916) 803-0268

National Air Balance Co., Inc.  
Fremont, California  
(510) 623-7000

Pacific Test and Balance, Inc.  
Fairfield, CA  
(707) 696-2444

Penn Air Control, Inc.  
Cypress, California  
(714) 220-9091

Penn Air Control, Inc.  
Fallbrook, California  
(760) 451-2025

RSAnalysis, Inc.  
El Dorado Hills, California  
(916) 358-5672

San Diego Air Balance, Co., Inc.  
Escondido, California  
(760) 741-5401

Winair, Inc.  
Huntington Beach, California  
(714) 901-2747

## COLORADO

Proficient Balancing Company, LLC  
Arvada, Colorado  
(303) 870-0249

## CONNECTICUT

CFM Test & Balance Corporation  
Bethel, Connecticut  
(203) 778-1900

James E. Brennan Company, Inc.  
Wallingford, Connecticut  
(203) 269-1454

## FLORIDA

Air Balance Unlimited, Inc.  
Sorrento, Florida  
(407) 383-8259

Air Proserv, Inc.  
Boca Raton, Florida  
(561) 208-3882

ecoTAB, LLC  
Sarasota, Florida  
(941) 926-2916

Gregor Hartenhoff, Inc.  
Pompano Beach, Florida  
(954) 786-3420

Perfect Balance Inc.  
Jupiter, Florida  
(561) 575-4919

Precision Balance, Inc.  
Orlando, Florida  
(407) 876-4112

Professional Air Balancing, Inc.  
Clearwater, Florida  
(727) 592-9666

Southern Balance, Inc.  
Milton, Florida  
(850) 623-9229

Southern Independent Testing Agency, Inc.  
Lutz, Florida  
(813) 949-1999

Test and Balance Corporation  
Lutz, Florida  
(813) 909-8809

The Phoenix Agency, Inc.  
Lutz, Florida  
(813) 908-7701

Thermocline Corp.  
Merritt Island, Florida  
(321) 453-3499

## GEORGIA

Addison Energy Technologies, LLC  
Toccoa, Georgia  
(706) 244-0383

Augusta Air Balance Company, LLC  
Martinez, Georgia  
(706) 799-2254

Southern Balance Company  
Marietta, Georgia  
(770) 850-1027

TAB Services, Inc.  
Norcross, Georgia  
(404) 329-1001

Test and Balance Corporation  
Roswell, Georgia  
(678) 393-9401

## GUAM

Penn Air Control, Inc.  
Tamuning, Guam  
(671) 477-0325

## HAWAII

Penn Air Control, Inc.  
Aiea, Hawaii  
(808) 492-1640

Test and Balance Corp. of the Pacific  
Honolulu, Hawaii  
(808) 593-1924

## ILLINOIS

United Building & Energy Services, LLC  
Wheaton, Illinois  
(630) 790-4940

## INDIANA

Fluid Dynamics, Inc.  
Fort Wayne, Indiana  
(260) 490-8011

Synergy Test & Balance, Inc.  
Indianapolis, Indiana  
(317) 222-1828

## IOWA

Systems Management & Balancing, Inc.  
Waukee, Iowa  
(515) 987-2825

## KENTUCKY

Thermal Balance, Inc.  
Ashland, Kentucky  
(606) 325-4832

Thermal Balance, Inc.  
Nicholasville, Kentucky  
(859) 277-6158

Thermal Balance, Inc.  
Paducah, Kentucky  
(270) 744-9723

## LOUISIANA

Coastal Air Balance Corp.  
Metairie, Louisiana  
(504) 834-4537

Tech-Test Inc. of Louisiana  
Baton Rouge, Louisiana  
(225) 752-1664

## MARYLAND

American Testing Inc.  
Ellicott City, Maryland  
(410) 461-6211

Baumgartner, Inc.  
Hunt Valley, Maryland  
(410) 785-1720

Chesapeake Testing & Balancing Engineers, Inc.  
Easton, Maryland  
(410) 820-9791

Environmental Balancing Corporation  
Clinton, Maryland  
(301) 868-6334

Performance Test and Balance, LLC  
Bowie, Maryland  
(301) 809-0100

Protab, Inc.  
Hampstead, Maryland  
(410) 935-8249

Test & Balancing, Inc.  
Laurel, Maryland  
(301) 953-0120

## MASSACHUSETTS

Thomas-Young Associates, Inc.  
Marion, Massachusetts  
(508) 748-0204

## MICHIGAN

Aerodynamics Inspecting Co.  
Dearborn, Michigan  
(313) 584-7450

Airflow Testing, Inc.  
Lincoln Park, Michigan  
(313) 382-8378

Air Solutions Inc.  
Lapeer, Michigan  
(810) 358-8644

## MINNESOTA

Air Systems Engineering, Inc.  
Minnetonka, Minnesota  
(952) 807-6744

Mechanical Data Corporation  
Bloomington, Minnesota  
(952) 473-1176

Mechanical Test and Balance Corporation  
Maple Plain, Minnesota  
(763) 479-6300

SMB of Minnesota  
Blaine, Minnesota  
(763) 398-3284

## MISSISSIPPI

Capital Air Balance, Inc.  
Terry, Mississippi  
(601) 878-6701

Coastal Air Balance Corp.  
Terry, Mississippi  
(228) 392-8768

## MISSOURI

Miller Certified Air, Inc.  
St. Louis, Missouri  
(314) 352-8981

Precisionaire of the Midwest, Inc.  
Grain Valley, Missouri  
(816) 847-1380

Senco Services Corporation  
St. Louis, Missouri  
(314) 432-5100

Testing & Balance Co. of the Ozarks, LLC (TABCO)  
Ozark, Missouri  
(417) 443-4430

## NEVADA

American Air Balance Co., Inc.  
Las Vegas, Nevada  
(702) 255-7331

Mechanical Test and Balance Corporation  
Las Vegas, Nevada  
(702) 737-3030

Penn Air Control, Inc.  
Las Vegas, Nevada  
(702) 221-9877

Raglen System Balance, Inc.  
Reno, Nevada  
(775) 747-0100

RSAnalysis, Inc.  
Las Vegas, Nevada  
(702) 740-5537

## NEW JERSEY

Airology  
Bridgewater, New Jersey  
(908) 722-1776

Effective Air Balance, Inc.  
Totowa, New Jersey  
(973) 790-6748

National Air Balance Company LLC  
Paramus, New Jersey  
(201) 444-8777

## NEW YORK

Mechanical Testing, Inc.  
Saratoga Springs, New York  
(518) 450-7292

Mechanical Testing, Inc.  
Binghamton, New York  
(607) 722-1819

Precision Testing & Balancing, Inc.  
Brooklyn, New York  
(718) 994-2300

## NORTH CAROLINA

Building Environmental Systems Testing, Inc. (BEST, Inc.)  
Wilson, North Carolina  
(252) 291-5100

e-nTech Independent Testing Services, Inc.  
Winston-Salem, North Carolina  
(336) 896-0090

Palmetto Air & Water Balance, Inc.  
Charlotte, North Carolina  
(704) 587-7073

Palmetto Air & Water Balance, Inc.  
Greensboro, North Carolina  
(336) 275-6678

Palmetto Air & Water Balance, Inc.  
Raleigh, North Carolina  
(919) 460-7730

Palmetto Air & Water Balance, Inc.  
Wilmington, North Carolina  
(910) 202-3850

The Phoenix Agency of North Carolina, Inc.  
Winston-Salem, NC  
(336) 744-1998

## NORTH DAKOTA

Design Control, Inc.  
Fargo, North Dakota  
(701) 237-3037

## OHIO

Air Balance Unlimited, Inc.  
Gahanna, Ohio  
(614) 595-9619

Kahoe Air Balance Company  
Cleveland, Ohio  
(440) 946-4300

Kahoe Air Balance Company  
Cincinnati, Ohio  
(513) 248-4141

Kahoe Air Balance Company  
Columbus, Ohio  
(614) 694-2558

PBC, Inc.  
(Professional Balance Co.)  
Willoughby, Ohio  
(440) 975-9494

## AABC CANADIAN CHAPTER

Precision Air Balance Company, Inc.  
Cleveland, Ohio  
(216) 362-7727

R.H. Cochran and Associates, Inc.  
Wickliffe, Ohio  
(440) 585-5940

### OKLAHOMA

Eagle Test & Balance  
Cushing, Oklahoma  
(918) 225-1668

### OREGON

Northwest Engineering Service, Inc.  
Tigard, Oregon  
(503) 639-7525

Pacific Coast Air Balancing  
Newberg, Oregon  
(503) 537-0826

### PENNSYLVANIA

Butler Balancing Company, Inc.  
Thorndale, Pennsylvania  
(610) 873-6905

Flood and Sterling Inc.  
New Cumberland, Pennsylvania  
(717) 232-0529

Kahoe Air Balance Company  
Pittsburgh, Pennsylvania  
(724) 941-3335

WAE Balancing, Inc.  
Mercer, Pennsylvania  
(724) 662-5743

### PUERTO RICO

Penn Air Control, Inc.  
Naguabo, Puerto Rico  
(787) 874-3612

### SOUTH CAROLINA

Palmetto Air & Water Balance, Inc.  
Greenville, South Carolina  
(864) 877-6832

Palmetto Air & Water Balance, Inc.  
Charleston, South Carolina  
(843) 789-5550

### TENNESSEE

Environmental Test & Balance Company  
Memphis, Tennessee  
(901) 373-9946

Systems Analysis, Inc.  
Hermitage, Tennessee  
(615) 883-9199

Thermal Balance, Inc.  
Nashville, Tennessee  
(615) 768-5461

United Testing & Balancing, Inc.  
Nashville, Tennessee  
(615) 331-1294

United Testing & Balancing, Inc.  
Knoxville, Tennessee  
(865) 922-5754

### TEXAS

Aerodynamics Inspecting Co.  
Houston, Texas  
(281) 481-2100

Aerodynamics Inspecting of Texas, LLC  
San Juan, Texas  
(956) 510-8022

Air Balancing Company, Inc.  
Fort Worth, Texas  
(817) 572-6994

AIR Engineering and Testing, Inc.  
Dallas, Texas  
(972) 386-0144

Austin Air Balancing Corporation  
Austin, Texas  
(512) 477-7247

Delta-T, Ltd.  
Garland, Texas  
(972) 494-2300

Delta-T, Ltd.  
Austin, Texas  
(512) 590-1051

Engineered Air Balance Co., Inc.  
Richardson, Texas  
(972) 818-9000

Engineered Air Balance Co., Inc.  
San Antonio, Texas  
(210) 736-9494

Engineered Air Balance Co., Inc.  
Spring, Texas  
(281) 873-7084

National Precisionaire, LLC  
Houston, Texas  
(281) 449-0961

Online Air Balancing Company  
Houston, Texas  
(713) 453-5497

PHI Service Agency, Inc.  
San Antonio, Texas  
(210) 224-1665

PHI Service Agency, Inc.  
Austin, Texas  
(512) 339-4757

PHI Service Agency, Inc.  
Alamo, Texas  
(956) 781-9998

PHI Service Agency, Inc.  
Corpus Christi, Texas  
(361) 248-4861

Professional Balancing Services, Inc.  
Dallas, Texas  
(214) 349-4644

TAB Solutions, Inc.  
Lakeway, Texas  
(720) 220-1062

Technical Air Balance, Texas  
Spring, Texas  
(281) 651-1844

Texas Test & Balance  
Houston, Texas  
(281) 358-2118

### UTAH

Mechanical Testing Corporation  
Leeds, Utah  
(435) 879-9284

RSAnalysis, Inc.  
Sandy, Utah  
(801) 255-5015

### VIRGINIA

Arian Tab Services  
Herndon, Virginia  
(703) 319-1000

C&W-TESCO, Inc.  
Richmond, Virginia  
(804) 379-9345

Mid-Atlantic Test & Balance, Inc.  
South Boston, Virginia  
(434) 572-4025

### WASHINGTON

Eagle Test & Balance  
Bellevue, Washington  
(425) 747-9256

TAC Services, LLC  
Bellingham, Washington  
(360) 224-8555

### WISCONSIN

Professional System Analysis, Inc.  
Germantown, Wisconsin  
(262) 253-4146

### MANITOBA

A.H.S. Testing & Balancing Ltd.  
Winnipeg, Manitoba  
(204) 224-1416

Air Movement Services Ltd.  
Winnipeg, Manitoba  
(204) 233-7456

AIRDRONICS, Inc.  
Winnipeg, Manitoba  
(204) 253-6647

D.F.C. Mechanical Testing & Balancing Ltd.  
Winnipeg, Manitoba  
(204) 694-4901

### NEW BRUNSWICK

Controlled Air Management Ltd.  
Moncton, New Brunswick  
(506) 852-3529

Scan Air Balance 1998 Ltd.  
Moncton, New Brunswick  
(506) 857-9100

Source Management Limited  
Hanwell, New Brunswick  
(506) 443-9803

### NOVA SCOTIA

Griffin Air Balance Ltd.  
Dartmouth, Nova Scotia  
(902) 434-1084

Scotia Air Balance 1996 Limited  
Antigonish Co., Nova Scotia  
(902) 232-2491

### ONTARIO

Accu-Air Balance Co.  
(1991) Inc.  
Windsor, Ontario  
(519) 256-4543

Air & Water Precision Balancing, Inc.  
Toronto, Ontario  
(647) 896-5353

Airwaso Canada Inc.  
London, Ontario  
(519) 652-4040

Caltab Air Balance Inc.  
Tecumseh, Ontario  
(519) 259-1581

Designest & Balance Co. Ltd.  
Richmond Hill, Ontario  
(905) 886-6513

Dynamic Flow Balancing Ltd.  
Oakville, Ontario  
(905) 338-0808

Kanata Air Balancing & Engineering Services  
Ottawa, Ontario  
(613) 832-4884

Pro-Air Testing Inc.  
Toronto, Ontario  
(416) 252-3232

Vital-Canada Group Inc.  
Mississauga, Ontario  
(905) 848-1000

VPG Associates Limited  
King City, Ontario  
(905) 833-4334

## AABC INTERNATIONAL MEMBERS

### ITALY

Studio S.C.S. Ingegneri  
Scarbaci-Cuomo  
Pordenone, ITALY  
+39-0434-29661

### KUWAIT

Molden Technical & Consulting Projects Co.  
Sharq, Kuwait  
+965-22282020

### SOUTH KOREA

Awin ENC Co., Ltd.  
Soengdong-gu, Seoul  
South Korea  
+82-2-2117-0290

Energy 2000 Technical Engineering Co., Ltd.  
Songpa-gu, Seoul  
South Korea  
+82-2-408-2114

Kyungmin Fne  
Gangbuk-gu, Seoul  
South Korea  
+82-2-7077-9447-33



# Have an Opinion?

## An interesting case study? A new method? Tell us about it.

TAB Journal welcomes submissions for publication.  
TAB Journal is published quarterly by the Associated  
Air Balance Council. Send letters or articles to:

Editor • TAB Journal  
1518 K Street, NW, Suite 503  
Washington, DC 20005 • [info@aabcc.com](mailto:info@aabcc.com)



# ACCURATE. DEPENDABLE. VERSATILE.

TSI provides the most accurate, dependable and versatile **ventilation and indoor air quality measurement instruments** on the market today.

+ **EBT731 Balometer® Capture Hood**

+ **Hydronic Manometers**

+ **VelociCalc® Air Velocity Meter**

+ **Complete Portfolio of IAQ Instruments**

Trust TSI as your one stop source for instrumentation to save time and money on the jobsite.

Visit [www.tsi.com/comfort](http://www.tsi.com/comfort) for more information.



NEW

AirAssure™  
PM2.5 Indoor  
Air Quality  
Monitor



UNDERSTANDING, ACCELERATED

